

## AMPLIFICADORES - MEZCLADORES CON SEGURIDAD DE AVISOS

**AXD-30** 30 W

**AXD-60** 60 W

**AXD-120** 120 W

**AXD-240** 240 W

Amplificadores con salida de línea de 100, 70 y 50 V, así como de baja impedancia (4, 8 y 16 ohm), para su aplicación en toda clase de instalaciones fijas de megafonía, para distribución de música y emisión de avisos prioritarios. Incorporan protección térmica y relé de seguridad de avisos (para gestión de atenuadores). Disponen de una ranura para insertar tarjetas de ampliación de funciones (entrada de teléfono, avisos pregrabados...)



AXD-30



AXD-60  
AXD-120  
AXD-240

	AXD-30	AXD-60	AXD-120	AXD-240
Alimentación	230 V CA / 24 V CC, 50/60 Hz	230 V CA / 24 V CC, 50/60 Hz	230 V CA / 24 V CC, 50/60 Hz	230 V CA / 24 V CC, 50/60 Hz
Potencia	30 W	60 W	120 W	240 W
Salidas altavoces	100, 70, 50 V ó 4, 8, 16 ohm	100, 70, 50 V ó 4, 8, 16 ohm	100, 70, 50 V ó 4, 8, 16 ohm	100, 70, 50 V ó 4, 8, 16 ohm
Entradas micrófono	2 x -60 dB, simétrica, XLR	5 x -60 dB, simétrica, XLR	5 x -60 dB, simétrica, XLR	5 x -60 dB, simétrica, XLR
Entradas auxiliar (2)	150 mV ~ 1 V, asimétrica, RCA	150 mV ~ 1 V, asimétrica, RCA	150 mV ~ 1 V, asimétrica, RCA	150 mV ~ 1 V, asimétrica, RCA
Entrada emergencia EMG	asimétrica, 0 dB, RJ45	asimétrica, 0 dB, RJ45	asimétrica, 0 dB, RJ45	asimétrica, 0 dB, RJ45
Función de prioridad	EMG>MIC1>MIC2>AUX	EMG>MIC1>MIC2>AUX	EMG>MIC1>MIC2>AUX	EMG>MIC1>MIC2>AUX
Respuesta en frecuencia	50 ~ 18.000 Hz	50 ~ 18.000 Hz	50 ~ 18.000 Hz	50 ~ 18.000 Hz
Otras prestaciones	phantom, gong, mixer, relé	phantom, gong, mixer, relé	phantom, gong, mixer, relé	phantom, gong, mixer, relé
Dimensiones (mm)	430 x 89 x 250 (2 u)	430 x 89 x 280 (2 u)	430 x 89 x 290 (2 u)	430 x 89 x 380 (2 u)
Peso	6,0 kg	7,5 kg	9,0 kg	13,0 kg

### Interfaz telefónico

#### AXD-TEL

Interfaz telefónico DTMF para acceso a megafonía desde la instalación de telefonía (línea o extensión analógica, marcación DTMF). Con ajuste de volumen y prioridad máxima (excepto emergencia).



### Reproductor de mensajes

#### AXD-MP3

Reproductor de mensajes en formato MP3 con capacidad de almacenamiento de hasta 255 mensajes, con activación remota o desde placa frontal, ajuste de volumen y prioridad máxima (excepto emergencia).



## MIXER AMPLIFIERS WITH SECURITY PAGING

- AXD-30** 30 W
- AXD-60** 60 W
- AXD-120** 120 W
- AXD-240** 240 W

Amplifiers with line output of 100, 70 and 50 V, and low impedance (4, 8 and 16 Ohm), for application in all kinds of fixed PA installations, for music distribution and broadcasting of priority announcements. Incorporating heat protection and security relay of announcements (for attenuator management). They have a slot to insert cards to extend functions (telephone input, pre-recorded announcements...)



AXD-30



AXD-60  
AXD-120  
AXD-240

	<b>AXD-30</b>	<b>AXD-60</b>	<b>AXD-120</b>	<b>AXD-240</b>
Power supply	230 Vac/24 Vdc, 50/60 Hz	230 Vac/24 Vdc, 50/60 Hz	230 Vac/24 Vdc, 50/60 Hz	230 Vac/24 Vdc, 50/60 Hz
Power	30 W	60 W	120 W	240 W
Loudspeaker outputs	100, 70, 50 V or 4, 8, 16 ohm	100, 70, 50 V or 4, 8, 16 ohm	100, 70, 50 V or 4, 8, 16 ohm	100, 70, 50 V or 4, 8, 16 ohm
Microphone inputs	2 x -60 dB, balanced, XLR	5 x -60 dB, balanced, XLR	5 x -60 dB, balanced, XLR	5 x -60 dB, balanced, XLR
Auxiliary inputs (2)	150 mV ~ 1 V, unbalanced, RCA	150 mV ~ 1 V, unbalanced, RCA	150 mV ~ 1 V, unbalanced, RCA	150 mV ~ 1 V, unbalanced, RCA
EMG emergency input	unbalanced, 0 dB, RJ45	unbalanced, 0 dB, RJ45	unbalanced, 0 dB, RJ45	unbalanced, 0 dB, RJ45
Priority function	EMG>MIC1>MIC2>AUX	EMG>MIC1>MIC2>AUX	EMG>MIC1>MIC2>AUX	EMG>MIC1>MIC2>AUX
Frequency response	50 ~ 18.000 Hz	50 ~ 18.000 Hz	50 ~ 18.000 Hz	50 ~ 18.000 Hz
Other services	phantom, gong, mixer, relay	phantom, gong, mixer, relay	phantom, gong, mixer, relay	phantom, gong, mixer, relé
Dimensions (mm)	430 x 89 x 250 (2 u)	430 x 89 x 280 (2 u)	430 x 89 x 290 (2 u)	430 x 89 x 380 (2 u)
Weight	6,0 kg	7,5 kg	9,0 kg	13,0 kg

### Telephone interface

#### AXD-TEL

DTMF telephone interface for access to PA from the telephone installation (analogue line or extension, DMTF dialling). With volume adjustment and maximum priority (except for emergency).



### Message player

#### AXD-MP3

MP3 message player with storage capacity of up to 255 messages, with remote activation or from front plate, volume adjustment and maximum priority (except for emergency).

