

# **ACA-BL05SS-100**

LHD Cable Accessory - Bracket "L", 50mm (2") (St Steel) w/ Sleeve - Qty100

### L-Bracket

The ACA-BL series L-brackets is designed to support linear heat cable above the risk area e.g. the top run of a cable tray. A silicon protection sleeve is supplied with the unit to protect the sensor cable when fastened to the bracket.

#### Installation

The ACA-BL may be fitted to the cable tray and secured in place using a suitable bolt and nut at one end. The hole at the other end of the bracket allows for the securing of the sensor cable using a silicone sleeve and cable tie. The L-bracket allows support for the sensor cable at the selected distance away from the detection area.

Recommended spacing: 1m



#### **Standard Features**

- Easy installation of linear heat cable
- For use on cable trays
- · Available in stainless steel
- Available in quantities of 100

# ACA-BL05SS-100

LHD Cable Accessory - Bracket "L", 50mm (2") (St Steel) w/ Sleeve - Qty100

### **Specifications**

Physical	
Physical dimensions	20 x 50 mm (W x L)
Net weight	1.05 kg
Material	Stainless Steel
Environmental	
Environment	Indoor, Outdoor
- ACA-BL05SS-100	
Dimensions (I x w)	50 x 20mm
Weight	1.05kg
Material	Stainless Steel
Quantity	100

