

ACL760

Vandal proof standalone keypad slim housing

Standalone vandal-proof keypad

Mullion and vandal-resistant access control keypad with metal keys for doorframe mounting. With user memory of 99 codes and one push button, ACL760 is the best solution for single door access control. Photoelectric sensor for automatic illumination is effective in low-lit conditions. ACL760 with a rugged good look is designed to operate even in harsh environments.



Details

- Indoor/outdoor
- Dust proof and water-resistant
- Up to 99 user codes
- Up to 3 peripherals (keypad/proximity reader) can be connected
- Codes can be 1 to 8 digit long

ACL760

Vandal proof standalone keypad slim housing

Technical Specifications

General

User Interface	Touch Buttons
----------------	---------------

Communication

Communication Type	Wired
--------------------	-------

Electrical

Operating voltage	12/24 VAC/DC
Power supply type	VAC
Current consumption	70 mA max

Physical

Form factor	Vertical
Mounting Type	Surface Mount

Environmental

Operating temperature	-25 to 60 °C
Relative humidity	0 to 95% non-condensing

Supply voltage

12/24 VAC/DC

Current consumption

70 mA max

Outputs

Relays	1 relay and 1 transistors
--------	---------------------------

Operating temperature

-25 °C to +70 °C

Operating humidity

0 to 95% (non-condensing)

Cabel

3 m

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

8 June 2018 - 12:59 PM