#### **Product data sheet**



## ACL805FLW-S

#### ACL800 Keypad - Wiegand, Flush mount, Silver, Electronic only (no frame included)

#### **Product description**

The ACL805FLW is a Multiprotocol digital keypad for access control applications with backlight keys and a selectable output protocol. These flush mount keypads are designed to fit a DIN electrical back box and are available in three different color finishes. It offers programmable Wiegand protocols for easy integration with standard access systems. The tamper switch output can trigger the alarm system, if an attempt is made to open or remove the unit from the wall.

#### The ACL800 range

The ACL805FLW is a Multiprotocol digital keypad for access control applications with backlight keys and a selectable output protocol. These flush mount keypads are designed to fit a DIN electrical back box and are available in three different color finishes. It offers programmable Wiegand protocols for easy integration with standard access systems. The tamper switch output can trigger the alarm system, if an attempt is made to open or remove the unit from the wall.

#### Card technology

The readers are compatible with the TruPortal (125 KHz) credential range and other industry standards like MIFARE Classic, - Plus, - Ultralight and - DESFire EV1. These technologies use the CSN (Card Serial Number) or UID (Unique Identifier) as credential identifier. The wiegand output (32 or 56 bit) is automatic according to the card type and ensures uniqueness of the MIFARE CSN with 4 and 7 Byte UID. The Proximity card type can be selected through DIP switches in "HID only", "HID and EM", "HID and Casi", "Casi only" or "EM only" and Wiegand outputs automatically according to the card type.

#### Compatibility

The ACL800 reader range is compatible with the TruPortal learn-in reader (TP-RDR-LRN) for learning-in credentials in access control panels like TruPortal. This compatibility is provided for both the 125 KHz and the 13.56 MHz credentials, while using the full wiegand format length in the management software (also with other third-party packages). There are different mounting possibilities: either flush mounted within the electrical wall sockets or surface mounted with a stylish, small, modern-looking molded design.



#### Details

- Indoor (IP40)
- Attractive and timeless design
- Includes a buzzer
- Tri-color LED's
- Flush mount
- Replaceable cover frames available in multiple colors to easily blend into a contemporary lifestyle
- The cover frames are available in single or dual, vertical or horizontal to combine different technologies side-by-side
- The built-in tamper construction provides additional pry-off security
- Backlight illumination
- PIN Code length is from 1 to 8 digits

# ACL805FLW-S

### ACL800 Keypad - Wiegand, Flush mount, Silver, Electronic only (no frame included)

#### **Technical specifications**

| Technology Reader type        | Interface  |
|-------------------------------|--|
| Communication                 |  |
| protocols                     | Compatible with Wiegand 26, 30, 34, 40, 42, 58 bit, Clock & Data or 8bit per key |
| System                        |  |
| Max. reader distance to panel | 50 m   |
| RTE (Request To Exit)         | No   |
| CSN (Card Serial<br>Number)   | No   |
| No. of LEDs                   | 3  |
| Interface & connect           | tions  |
| Interface                     | Wiegand  |
| Connector type                | Terminal Strip   |
| Tamper type                   |  |
| Pry-off tamper                | Yes  |
| Opening tamper                | Yes  |
| Tamper protection             | When open or dismantled  |
| Operation                     |  |
| Stand-alone                   | Yes  |
| Stand-alone no. of users      | 99   |
| PIN keypad                    | Yes  |
| PIN length                    | 1 to 8 digits  |
| Keys                          | Backlit metallic   |
| Green LED                     | Externally controlled  |
| Red LED                       | Externally controlled  |
| Orange LED                    | Programming status   |
| Illumination                  | Blue backlight (programmable on/off control)                                     |
| Buzzer                        | 1  |
| Support                       |  |
| Language installation manual  | English  |
| Electrical                    |  |
| Power supply type             | VDC  |
| Power supply value            | 9 to 14V DC  |
| Current consumption           | Max. 70mA @ 12 VDC   |
| Physical                      |  |
| Physical dimensions           | 80 x 80 x 9 mm   |
| Net weight                    | 70 g   |
| Shipping weight               | 200 g  |
| Colour                        | Silver   |
| Material                      | ABS  |
| Form factor                   | EMEA gangbox   |
| Mounting type                 | Flush Mount  |
| Environmental                 |  |
| Storage temperature           | -20 to +50°C   |

#### Standards & regulation

| Compliancy | CE, RoHS |
|------------|----------|
|            |          |

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

Indoor



Environment