

# ACL875SU-BS-S

## ACL800 Biometric Swipe reader with Keypad - Fingerprint, Stand alone, Surface mount, 100 Templates, Silver

### Product description

These surface mount ACL875SU-BS readers includes a buzzer and a tri-color LED for state indication (access granted, access denied or idle). The ACL875SU-BS is a simple one-door standalone biometric system (or 2 doors when used with ACL870FL-PB-S) with two-factor authentication. If a secure installation is needed, the reader can be connected to a ACL800FL-RU2-W remote relay unit in a secured area, which also plays the role of a Request-To-Exit button. The complete setup and programming can be done by scrolling and tapping on the sensor.

### The ACL800 range

The ACL800 Series consists of all the required elements to establish a range with a state-of-the-art design. This new range, consisting of readers, stand-alone keypad readers and Request-To-Exit touch sensitive push buttons, provides all you need for a coherent look-and-feel attractive project. The product line has now expanded new biometric readers.

### Card technology

The readers are compatible with the TruPortal (125 KHz) credential range and other industry standards like MIFARE Classic, - Plus, - Ultralight and - DESFire EV1. These technologies use the CSN (Card Serial Number) or UID (Unique Identifier) as credential identifier. The wiegand output (32 or 56 bit) is automatic according to the card type and ensures uniqueness of the MIFARE CSN with 4 and 7 Byte UID. The Proximity card type can be selected through DIP switches in "HID only"

### Compatibility

The ACL800 reader range is compatible with the TruPortal learn-in reader (TP-RDR-LRN) for learning-in credentials in access control panels like TruPortal. This compatibility is provided for both the 125 KHz and the 13.56 MHz credentials, while using the full wiegand format length in the management software (also with other third-party packages). There are different mounting possibilities: either flush mounted within the electrical wall sockets or surface mounted with a stylish, small, modern-looking molded design.



### Details

- Indoor/outdoor
- Dust proof and water-resistant (IP65)
- Attractive and timeless design
- Includes a buzzer
- Tri-color LED's
- Surface mount
- Backlight illumination
- Simple one-door standalone biometric system
- Reader programming is quick and easy

# ACL875SU-BS-S

## ACL800 Biometric Swipe reader with Keypad - Fingerprint, Stand alone, Surface mount, 100 Templates, Silver

### Technical specifications

#### Technology

Reader type	BioMetric
-------------	-----------

#### System

Max. reader distance to panel	50 m
RTE (Request To Exit)	Yes
CSN (Card Serial Number)	No
No. of LEDs	3
No. of covers included	1

#### Biometric

Biometric type	Fingerprint
Biometric template storage size	100 fingerprints (98 users and 2 for programming)
Biometric Sensor Type	Swipe Capacitive
Programming	1x Admin and 1x Installer finger

#### Interface & connections

Connector type	Pigtail
Pigtail length	100 cm
Output	One relay NO/NC contacts
Output maximum current	2A, 24 VAC/VDC

#### Tamper type

Pry-off tamper	No
Opening tamper	Yes

#### Operation

Stand-alone	Yes
Stand-alone no. of users	100
PIN keypad	Yes
PIN length	1 to 8 digits
Green LED	Potential Free
Red LED	Potential Free
Orange LED	Idle mode
Illumination	Blue backlight (programmable on/off control)
Buzzer	1
Door time	Pulse (1-30 s) or Toggle (ON/OFF)
Entry mode	Finger or PIN Code

#### Support

Language installation manual	English
------------------------------	---------

#### Electrical

Power supply type	VDC
Power supply value	9 to 14 VDC
Current consumption	150 mA at 12 VDC max

#### Physical

Physical dimensions	100 x 94 x 30 mm
Net weight	491 g
Shipping weight	760 g
Colour	Silver
Material	Moulded aluminium
Form factor	Oversized
Mounting type	Surface Mount

#### Environmental

Operating temperature	-20 to +50°C
Storage temperature	-20 to +50°C
Environment	Indoor / Outdoor

#### Standards & regulation

Compliance	CE, RoHS
------------	----------

