### **Product data sheet**



# ACT407E

(25 PACK) Mifare Classic card S50 with 7-byte UID serial number (CSN)

#### **Product overview**

These Mifare Classic1k cards are to be used on ATS1160N/ATS1161N, ACI406/ACI407 and any other UTC Fire & Security Mifare or Transition reader supporting 7-byte Card Serial Numbers (CSN). The cards are unprogrammed and only the unique 7-byte ID-number of the Mifare® chip, the so called Chip or Card Identification Number (CSN) is used by the readers.

#### **Details**

- Read only for CSN (7-byte)
- Read / Write function for card sectors
- Packed by 25

## ACT407E

### (25 PACK) Mifare Classic card S50 with 7-byte UID serial number (CSN)

### **Technical specifications**

Technology	
Credential type	Proximity
Credential operating	13.56 MHz
frequency	
Supported technology	MIFARE Classic (CSN)
13.56 MHz	
System	
Reading distance	0 to 10 cm
Memory size	1K
No. of Mifare bytes CSN	7 Byte (S50)
Supported readers	ACI406/407 Mifare Readers, ATS1160/1161
	Mifare Readers
Ordering information	
Cards/tags in package	25
Physical	
Material	PVC
Form factor	CR80 (Credit)
Physical dimensions	86 x 54 mm
Colour	White

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

