

ATS1197

Smart card reader with keypad supplied with 2 m cable

Product Overview

The ATS smart card readers connect directly on the RS485 data bus of the control panel or 4 Door Controller and may be configured and addressed via a LCD keypad. Some security options (Site code & 4-byte security code) are only programmable via TITAN and configuration cards. Mainly used for outdoor applications in high security sites where needs to be used a combination of a card and PIN for access.



Security features

The ATS smart card technology has the ability to programme a unique 4 billion, 4-byte, combination security code. This allows the memory card to unlock/open/disarm based on three keys; the card number, the Site code and the 4-byte security code. Once a 4-byte security code has been created, downloaded to the programmer and the cards, it is not possible to read the memory on the card or even recognise the card memory at any other reader or TITAN and programmer combination. Communications between TITAN and the programmer may also be password protected to prevent the 4-byte security code from being uploaded from the programmer into another PC running TITAN.

Details

- Full epoxy filled weather proof construction
- Keypad

Read/write encryption

The ATS Smart card technology also features an exclusive read/write encryption. When a card is presented at a reader, data are downloaded into the reader, encrypted and re-written back into the card. The readers can also be configured to operate in stand-alone or connected to control devices like office equipment or vending machines. This function enables credits to be assigned on user cards and deducted by the readers, purely on a usage basis. Up to 65535 credits may be allocated in up to 4 different banks with 16 access levels and 4 locations. The reader determines of which bank credits have to be deducted and the number of credits per valid presentation.

Multiple Card Badging

The ATS1197 can be used for arming/disarming areas as well as for access application. It is suitable for using the multiple card badging techniques which are available for the advisor MASTER control panel family. A user could arm the system in the evenings by badging his card three times within 10 seconds interval. Another application could be for doors which can be programmed so that badging once unlocks, badging twice with the same card keeps the door unlocked to allow people in and out without card, and badging three times re-locks the door.

ATS1197

Smart card reader with keypad supplied with 2 m cable

Technical Specifications

Technology

Reader Type	Proximity, Smart Card
Reader Operating- Transmitting Frequency	125 KHz
Supported Technology	125HiTag 2 KHz

Interface & connections

Interface	ATS RS-485
Pigtail Length	200

Inputs/outputs

Inputs	Request to exit
Outputs	1 Open Collector (50 mA)

Tamper type

Pry-Off Tamper	Yes
----------------	-----

Operation

PIN Keypad	Yes
------------	-----

Electrical

Operating voltage	8.5 to 14 VDC
Current consumption	40 mA typical 110 mA max.

Physical

Physical dimensions	140 x 121 x 22 mm
Colour	Dark grey
Mounting Type	Surface Mount

Environmental

Operating temperature	-40 to +50°C
Environment	Outdoor
IP-rating	IP66

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

8 June 2018 - 9:38 AM