

ATS1500A-IP-MM-HKG16



Standard Features

- 8 onboard zone inputs
- Max 32 zones: wired, wireless or mixed
- Economic input and output plug-in expansion
- Up to 16 shock sensor inputs
- 4 areas
- Up to 50 users
- EN50131 Grade 3 (when ATS-MM-TK added) / Environmental class 2
- USB port for local configuration
- Plug-on PSTN dialler for reporting or configuration
- Multilingual: language configurable per user
- Integrated 10/100Mb Ethernet connection
- IP alarm reporting to OH-NETREC receiver - Optional GPRS
- Integrated access control & support for ATS125x door controller

ATS1500A-IP-MM-HKG16

Specifications

System	
Product type	Intrusion
Panel type	Hybrid
No. of Keypads / Readers	16
Data Gathering Panels	15
No. of alarm groups	16
Specified cable	WCAT52 WCAT54
Inputs	
Inputs onboard	8
Inputs plug-in expansion	8
Max no. of inputs	between 1 and 32
Outputs	
No. of onboard Outputs	5
No. of outputs	128
Area	
No. of areas	between 1 and 4
User/Cards	
Maximum users	50
Users with name	50
Maximum cards	50
Maximum PIN codes	50
Communication	
Onboard Transmission Type	PSTN
Transmission Extension	GSM/GPRS
Databus Type	RS485
Event log	
Alarm event log	1000
Access event log	1,000
Physical	
Housing	Medium Metal
Physical dimensions	315 × 388 × 85 mm
Environmental	
Environmental Class	Class II, indoor
Operating temperature	-10 to +55°C
Relative humidity	95%
IP-rating	30
Standards & regulation	
Compliance	CE
EN50131 Grade	Grade 3

Ordering Information

Part No.	Description
ATS1500A-IP-MM-HKG16	