CDVI Group



ELECTROMAGNETIC SHEARLOCKS


▶ A LARGE RANGE OF ELECTROMAGNETIC LOCKS SUITABLE FOR ALL YOUR NEEDS

CZ3000

Self-aligning shearlock









- Shearing force: 1,500kg.
- Complete with armature plate.
- Patented self-aligning mechanism.
- NO/NC monitored.
- Fail safe (Door unlocked when the power is cut).
- Ideal for narrow aluminium profiles.
- Mortice.
- Surface mount housing (Optional: KCZ3000).
- Built-in varistor (Electronic protection to eliminate back EMF).
- Dimensions (L x W x D):
- Electromagnetic lock = $230 \times 31.5 \times 27$ mm,
- Armature = $230 \times 30 \times 37$ mm,
- $KCZ3000 = 234.5 \times 35.5 \times 42 \text{ mm}.$
- Finish: aluminium/steel.
- Input voltage: 12/24V dc.
- Consumption:
 - 12V dc = 600mA
- -24V dc = 300mA.







CE Certification

CODE	REFERENCE	DESCRIPTION
F0535000006	CZ3000	30-MM SHEARLOCK ELECTROMAGNET 12/24V DC + MONITORED
F0535000007	KCZ3000	SURFACE MOUNT HOUSING FOR CZ3000

^{*} Refer to Limited Lifetime Warranty Conditions.

BS60

HIGH RESISTANCE TO VANDALISM

Recommended power supplies

ARD212