

# DC148S60

**Industrial surface mount contact, high security grade 3, white, cable 6m**

## Requirements for grade 3 magnetic contacts


---

The grade 3 magnetic contacts are high security contacts which do meet the following requirements: preciseness of opening distance, magnet polarisation, strength of the magnet

## Model with built in EOL resistors available

---

Though built in EOL resistors are not mandatory according to EN50131-2.6 requirements, Interlogix offers a model with built in EOL resistors for a quick installation (see how to Order information)



## Details

---

- EN 50131-2-6 Grade 3 and VDS certified
- 6m cable
- covers to be clipped
- Tamper protected

# DC148S60

Industrial surface mount contact, high security grade 3, white, cable 6m

## Technical specifications

### General

Application type	Surface Mount
Contact type	1 pin NC contact
Connectivity	LIYY 4 x 0.14 mm Cu tin-plated; Suitable for LSA IDC method of termination

### Wired/wireless

Wired-wireless	Wired
----------------	-------

### Electrical

Operating voltage	max. 40 V
Voltage	max 100V DC
Contact power	max 6W or 6 VA
Switching current	max 500mA
Contact resistance	max 0.15 Ohm

### Physical

Colour	White
Dimensions magnet	8 x 8 x 40 mm
Dimensions contact / sensor	54 x 13 x 12.5 mm
Operating gap	Non-steel door 19 mm, +/- 4 mm - Steel door 12 mm, +/- 4 mm

### Environmental

Operating temperature	-25 to 70°C
IP rating	IP67

### Standards & regulation

EN50131 grade	Grade 3
---------------	---------

