

DP652L

Apollo Series 65 Optical Smoke Detector With Blinking LED (55000-316)

General

The 650 Series smoke and heat detectors are designed for the highest effectiveness by utilising the latest technology.

Standard Base

The base is designed to enable detectors to be plugged in without any need for force - particularly useful when fitting to suspended ceilings. To make it even easier, the base has a "one way only" fit. All bases are lockable and contains no electronic parts that could be damaged during installation.

The detectors are polarity insensitive and bases are easy to wire with an earth connector.



Details

- Polarity insensitive
- Common base
- Elegant slim-line design
- EN54 approved
- Wide operating voltage

DP652L

Apollo Series 65 Optical Smoke Detector With Blinking LED (55000-316)

Technical specifications

General

Indicación de estado	LED (alarm)
----------------------	-------------

Eléctrico

Voltaje de funcionamiento	9 to 33 VDC
Consumo de corriente	40 µA at 24 V (typical) (quiescent)

Salida

Salida de alarma remota	17 mA (current)
-------------------------	-----------------

Físico

Dimensiones físicas	50 x 100 mm (Detector + base) (H x W) 42 x 100 mm (Detector) (H x W)
Color	Blanco

Medioambiental

Temperatura de funcionamiento	-20 to +60°C (no icing)
Humedad relativa	0 to 95% noncondensing
Entorno	Interior
Clasificación IP	IP43

Estándares y regulaciones

Certificación	EN54-7
---------------	--------

Max. wind

Not affected

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

Last updated on 20 August 2019 - 11:09

