

DS-D5043FL-B

43" FHD LCD Display Monitor



Hikvision's DS-D5043FL-B 43-inch FHD LCD monitor provides excellent color rendition and enhanced, 1080p resolution. It features an LED direct-lit backlight with uniform brightness and no boundary shadow.

The DS-D5043FL-B is constructed of high-quality components and materials for 24/7 use.


Available Models:
DS-D5043FL-B

- 1080p FHD Resolution
- LED Backlit Technology
- Wide Angle View: 178° (H)/178° (V)
- 3D Comb Filter
- 3D De-Interlace
- 3D Noise Reduction
- Multiple Inputs: HDMI, VGA, BNC, CVBS
- 3.5 mm Audio Input
- Highly Reliable 24h/Day Functioning

Specifications



DS-D5043FL-B	
Display	
Screen Size	42.5"
Active Display Area	37.04" x 20.84" (940.90 (H) mm x 529.25 (V) mm)
Backlight	LED
Pixel Pitch	0.163 (H) mm x 0.490 (V) mm
Bezel Width	1.10" (28 mm) (left side, right side, top), 1.24" (31.5 mm) (bottom)
Resolution	1920 x 1080
Brightness	450 cd/m ²
Viewing Angle	178° (H)/178° (V)
Color Depth	8 bit
Contrast Ratio	1200:1
Response Time	8 ms
Refresh Rate	60 Hz
Color Gamut	72% NTSC
Haze	1.00%
Reliability	7 x 24 H
Interface	
Video and Audio Input	VGA x 1, DVI x 1, HDMI x 1, BNC IN x 1 Audio In x 1
Video and Audio Output	BNC Out x 1 Built-In Audio x 2
Data Transmission Interface	USB x 1
Control Interface	RS-232 In x 1, RS-232 Out x 1
General	
Casing Material	SECC
VESA	400 (H) x 300 (V) mm, M6 x 12 (15.04" (H) x 11.81" (V))
Power Supply	100 to 240 VAC
Power Consumption	100 W
Standby Consumption	<0.5 W
Working Temperature	32° F to 104° F (0° C to 40° C)
Working Humidity	10% to 80% RH
Storage Temperature	-4° F to 140° F (-20° C to 60° C)
Storage Humidity	10% to 80% RH
Product Dimensions	39.32" x 23.24" x 3.08" (998.78 mm x 590.52 mm x 78.14 mm)
Package Dimensions	46.93" x 29.61" x 8.18" (1192 mm x 752 mm x 208 mm)
Net Weight	32.3 lbs (14.66 kg)
Gross Weight	40.3 lbs (18.28 kg)
Accessories	Remote control x 1, serial port adaptor x 1, carbon dry battery x 2, network cable x 1, power cable x 1, CD-ROM x 1

Interface



Interfaces	Description
BNC IN	CVBS Signal Input
BNC OUT	CVBS Signal Loop Out
HDMI IN	HDMI Digital Signal Input
DVI IN	DVI Signal Input
VGA IN	VGA Signal Input
Audio In	3.5 mm Audio Input
USB	USB Interface
RS-232 In	Serial Port Input
RS-232 Out	Serial Port Output
100 to 240 VAC	Power Supply
Switch	Power Switch

Accessories

	
DS-DM4255W Wall-Mounted Bracket	DS-DM4303B Base Bracket