

Eagle Eye Camera DM08

Indoor/Outdoor 4MPix Mini-Dome IP Camera, 2.8/3.6mm Lens, POE, IR



The Eagle Eye Camera DM08 is a high-performance small package 4 Mega Pixel indoor/outdoor camera with all the features necessary to get clarity under both day and night conditions. This model is both indoor and outdoor rated, with a built-in microphone. The camera comes preconfigured to securely operate with the Eagle Eye Cloud Security VMS and Eagle Eye CameraManager.

Key Features

- > 4 Mega Pixel
- > Mini-Dome, Integrated microphone
- > Durable All Aluminum Housing
- > Fixed lens 2.8mm or 3.6mm
- > Wide Dynamic Range
- > Night Vision Smart IR, IR LEDs, 15m range
- > Triple RTSP Streams

| Dimension Drawing | |
|--------------------------|-------------------|
| | \$6 86 99.5 |

| Camera | |
|-----------------------------|--|
| Pixels | 4 Mega Pixel |
| Resolutions | 2592×1520/2560×1440/2304×1296/ 1920×1080/1280×720 @25/30fps |
| Lens | 2.8mm or 3.6mm lens |
| Night Vision | IR LEDs with up to 15m range |
| Field of View | 100° |
| Dynamic Range | WDR (120dB) and HLC/BLC |
| Digital Noise Reduction | 2D/3D DNR with defog |
| Digital Image Stabilization | Automatic |
| Applications | Best for small indoor areas: stock room, lobby, hallways, elevators, IT closets, storage rooms, entrances, interview rooms |
| Image Sensor | 1/3" progressive scan CMOS |
| Iris | Fixed |
| Shutter Speed | 1/5s to 1/20000s |
| Min Illumination | Color 0.05Lux; IR ON 0 Lux |

| Digital Capabilities | |
|----------------------|---|
| Video Compression | H.265, H.264, and MJPEG |
| Audio Compression | G.711, RAW_PCM |
| Image Settings | Rotation, Saturation, Brightness, Contrast, Sharpness |
| Corridor mode | Yes |

| Setup | |
|---------------------|---|
| Eagle Eye Cloud VMS | Preconfigured with secure password, plug and play |
| Camera Settings | Fully Integrated with Eagle Eye Cloud VMS and Eagle Eye CameraManager |
| Cyber Secure | Eagle Eye Verified |

| Interface | |
|--------------|--|
| Ethernet | Waterproof RJ-45 Female 10/100 Base-T |
| Audio | 1Ch audio in, 1Ch audio out or built in Microphone |
| BNC output | Built-in CVBS output |
| Edge Storage | Micro SD/SDHC/SDXC slot, Max 128GB |

| Physical/Power | |
|-----------------------|--|
| Power | DC12V/Power Over Ethernet (IEEE 802.3af) |
| Power Consumption | 3.5W IR Off, 6W IR On |
| Operating Temperature | -30°C to +55°C |
| Operating Humidity | 0% - 90% RH |
| Waterproof | IP66 |
| Approvals | CE/FCC |
| Dimensions | Φ 99.5 x 99.5 x 63mm |
| Weight | 370 grams |
| Housing | All Aluminum, Pointable camera |

| Eagle Eye Part Numbers | |
|------------------------|---|
| EN-CDUM-008a | Eagle Eye Camera DM08 Outdoor Mini Dome 4Mpix, IR, IP66, 3.6mm Lens, POE |
| EN-CDUM-008b | Eagle Eye Camera DM08b Outdoor Mini Dome 4Mpix, IR, IP66, 2.8mm Lens, POE |
| EN-RRC01 | Eagle Eye Camera Rapid Replacement |
| EN-CABX-005 | Eagle Eye Camera Junction Box BX005 (DM08,DD05 to DD11 ,DE02)) |
| EN-CAWA-001 | Eagle Eye Camera Wall Arm WA001 (DM07,DD05,DE02,DM08) |
| EN-CAPM-001 | Eagle Eye Camera Pole Mount PM001 (BX002, BX003, BX004) |