

EST-W6

Fire wall aesthetic speaker Power: 6W, 100V

Overview

The EST-W6 is an elegant multi-function loudspeaker designed to guarantee the highest acoustic parameters. Its solid casing offers an effective protection against acts of vandalism. The loudspeaker can be mounted either on a wall or on a ceiling. Additionally, the EST-W6 can be fixed as an recessed speaker and therefore it is an ideal solution for rooms where aesthetic factors play a significant role.

The loudspeaker offers adjustable power regulation through connectivity to applicable transformer tapings thus allowing suitable acoustic pressure (the level of sound) within areas of sound emission adequately to the acoustic conditions existing in those areas.



Details

- Certificate of Conformity issued by CNBOP: 1438-CPR-XXXX
- Compliance with BS5839-8 standard (Thermal protection)
- Exceptionally easy and quick to mount
- Modern and elegant design
- High quality sound of both speech and music
- Ideal for on-wall or in-wall mounting

EST-W6

Fire wall aesthetic speaker Power: 6W, 100V

Technical specifications

Eléctrico

Consumo de corriente	6 W
Nivel de salida	84 dB

Físico

Dimensiones físicas	260 x 180 x 80 mm (W x H x D)
Peso neto	2.3 kg
Color	Blanco (RAL 9003)
Tipo de Montaje	Montaje en pared
Posición de montaje	Pared
Material de la carcasa	Acero

Medioambiental

Temperatura de funcionamiento	-10°C / 55°C
Clasificación IP	32

Estándares y regulaciones

Normativas	EN54-24 BS5839-8 thermal protection 1438-CPR-0675 DC-UAE-0135
------------	--

Electrical


Rated power	6 W
Tappings 100 V line according to EN 54-24, W	6 / 3 / 1.5 / 0.75
Tappings 70 V line, W	3 / 1.5 / 0.75 / 0.375
Transformer impedance, Ω	1667 / 3333 / 6667 / 13333
Driver impedance	8 Ω
Effective frequency range	120-20 000 Hz
Sensitivity at 4 m, 1 W	80 dB
SPL at 4 m, Rated power	87 dB
SPL at 1 m, 1 W, Test signal bandwidth 300 Hz – 6 kHz	94 dB
SPL at 1 m, Rated power, Test signal bandwidth 300 Hz – 6 kHz	101 dB
Dispersion at 500 Hz / 1 kHz / 2 kHz / 4 kHz, [°]	180 / 180 / 163 / 80

Environmental

Environmental type / IP	A / IP21C
Rating according to EN 54-24	
Min / Max Amb Temp	-10°C to +55°C

Physical

Mounting	Screw
Optional for DC line monitoring	Capacitor
Colour optional	RAL Palette
Ease Model	



As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

Last updated on 15 July 2020 - 22:34

