

## FE110US

Eco Line Maglock 150 Kgf, unmonitored, surface mount



#### **Product Overview**

Eco Line mini magnetic lock. Surface mounting includes a quick mount bracket

### **Application**

Internal non high security doors and security cabinets

### Reliable security

This state of the art electro-magnetic locking device provides positive, instantaneous door control. Filler plates, angle brackets, and other mounting adapters are available to satisfy a wide range of door and frame types and conditions.

#### **Details**

- 150 Kgf holding force
- Not monitored
- No residual magnetism
- 12/24 V dc jumper selectable operation
- Mounts easily with a minimum of tools

# FE110US

Eco Line Maglock 150 Kgf, unmonitored, surface mount

### **Technical Specifications**

	~ r	-	ا م ،
G	er.	ıeı	a

Cicitoral	
Product type	Magnetic lock
Holding force	
Holding force kgf (Kilogram force)	150 kgf
Holding force N (Newton)	1500
Monitoring & status	
Monitored	No
LED indicator	No
Door status switch	No
Monitored changeover	No
Magnetic bond sensor	No
Electrical	
Power supply value	12 / 24 VDC
Current consumption	460 mA (+/- 2,5% @ 13,5 V)
Physical	
Physical dimensions	166 x 38 x 22 mm
Colour	Aluminium