

FE130MM

Eco Line magnetic lock 300 kgf, monitored, mortise mount



Eco Line mag 300 kgf, monitored. Mortise mounting.

Application

Medium Security applications for internal and external doors and transom housings.

Reliable Security

This state of the art electro-magnetic locking device provides positive, instantaneous door control. Filler plates, angle

brackets, and other mounting adapters are available to satisfy a wide range of door and frame types and conditions.

Safe operation

Our locking devices are inherently fail-safe, releasing instantly upon command or loss of power. With no moving parts to wear, stick or bind; no mechanical linkages to bend or break; and no bolt travel time or misalignment to raise concern, both unlocking and locking are always accomplished with ease and efficiency. As those electromagnetic locking devices function independently of any mechanical type locks, magnetic locks will not jeopardize the fire door rating of an opening.



Details

- 300 kgf holding power
- Monitored changeover
- No residual magnetism
- 12/24 V dc jumper selectable operation
- Mounts easily with a minimum of tools

FE130MM

Eco Line magnetic lock 300 kgf, monitored, mortise mount

Technical Specifications

	\sim	_	$\overline{}$	ra
しコ	\leftarrow	П	\leftarrow	ıaı

Product type	Magnetic lock		
Holding force			
Holding force kgf	300 kgf		
(Kilogram force)			
Holding force N (Newton)	3000		
Monitoring & status			
Monitored	Yes		
LED indicator	No		
Door status switch	No		
Monitored changeover	Yes		
Magnetic bond sensor	Yes		
Electrical			
Power supply value	12 / 24 VDC		
Current consumption	450 mA (+/- 2,5% @ 13,5 V)		
Physical			
Physical dimensions	228 x 38 x 27 mm		
Colour	Aluminium		
Finish	Vapour blasted aluminium		

