

PS-30TN

The LDA PS-30TN is an horn speaker certifiel in accordance to EN54-24, designed to cover big areas due to its high sensitivity and directivity.

It is made of ABS. For a increased protection, the loudspeaker is equipped with built in ceramic terminal and a thermal fuse. The power taps are 15 W / 10 W / 5 W / 8 Ω @100V or low impedance 8 Ohms.

It can be installed in outdoor, in wet applications, or indoor, providing reliable performance over wide temperature and humidity ranges.



Features of PS-30TNE:

- Horn speaker made in ABS with UV protection
- Power tap selector (70/100V lines)
- Bracket with U shape made of stainless steel.
- High sensitivity: 105dB (1W, 1m)

Technical Specifications:

Model	LDAPS30TNS01
NOMINAL POWER	15 W RMS
FREQUENCY RESPONSE	300 Hz -16 kHz +/-10dB
SENSITIVITY	105 dB (1 W, 1 m)
COLOUR	RAL9003
TRANSFORMER @ 70V/100V	15 W / 10 W / 5 W / 8Ω @100V 7.5 W / 5 W / 2.5 W / 8Ω @70V
BRACKET	U-bracket
MATERIAL	ABS con UV protección
DIMENSIONS (width x height x depth)	Ф213mm x 265 mm
WEIGHT	2,05 kg