DISTRIBUIDOR DE ANTENAS

UA-900

Distribuidor de señal de antena, rango de frecuencias UHF (470 a 870 MHz). Dos entradas de antena BNC 75 ohm, con alimentación phantom, cada una con cuatro salidas amplificadas (1,8 dB). Alimentación para cuatro receptores. Dimensiones 480 x 45 x 250 mm (1 u altura rack).

Frecuencia de portadora	470 ~ 870 MHz, UHF
Ganancia	1,8 dB
Aislamiento salida	>25 dB
Impedancia	50 Ω
Alimentación de receptor	12 ~ 18 V CC (4 conectores)
Alimentación antena	12 ~ 18 V CC
Alimentación	230 V CA, 50 ~ 60 Hz
Dimensiones	250 x 480 x 45 (1 u rack)
Peso	2,15 kg
Acabado	Plástico gris oscuro
Accesorios	4 x cables alimentación receptor

Receptores

US-902DC
US-8001DC

	US-902DC	US-8001DC
Rango de frecuencias	863 ~ 865 MHz, UHF	863 ~ 865 MHz, UHF
Capacidad	2 micrófonos	1 micrófono
Alimentación	12 V CC (adaptador), 500 mA	12 V CC (adaptador), 500 mA
Antena	Incorporadas / conectores BNC	Incorporadas
Salida de audio	-12 dB, sim (2 x XLR) asim (jack)	-12 dB, sim (XLR) asim (jack)
Selección de canales	Teclado y pantalla frontal	Conmutador frontal
Relación señal-ruido	Superior a 105 dB	Superior a 105 dB
Distorsión armónica total	Inferior al 0,6 % (a 1kHz)	Inferior al 0,6 % (a 1kHz)
Dimensiones (mm)	480 x 45 x 232 (1 u rack)	221 x 40 x 152
Respuesta en frecuencia	50 ~ 18.000 Hz, ±3 dB	50 ~ 18.000 Hz, ±3 dB

Antena de pared

UB-900

C/ Barcelona 101
17003 Girona (Spain)
(+34) 972 203 300

ANTENNA DISTRIBUTOR

UA-900

Antenna signal distributor, UHF frequency band (470-870 MHz). Two antenna inputs BNC 75 ohm with phantom power, each one with four amplified outputs (1.8 dB). Power supply for four receivers. Dimensions 480 x 45 x 250 mm (1 u rack height).

Carrier frequency	470 ~ 870 MHz, UHF
Gain	1,8 dB
Output isolation	>25 dB
Impedance	50 Ω
Receiver power supply	12 ~ 18 V dc (4 connectors)
Antenna power supply	12 ~ 18 V dc
Power supply	230 V CA, 50 ~ 60 Hz
Dimensions	250 x 480 x 45 (1 rack unit)
Weight	2,15 kg
Finish	Dark gray plastic
Accessories	4 x cables (receiver power supply)

Receivers

US-902DC
US-8001DC

	US-902DC	US-8001DC
Frequency range	863 ~ 865 MHz, UHF	863 ~ 865 MHz, UHF
Capacity	2 microphones	1 microphone
Power supply	12 Vdc (adapter), 500 mA	12 Vdc (adapter), 500 mA
Aerial	BNC connectors/incorporated	Incorporated
Audio output	-12 dB, sym (2 x XLR) assym (jack)	-12 dB, sym (XLR) assym (jack)
Channel selection	Keyboard and front display	Front switch
Signal-to-noise ratio	Over 105 dB	Over 105 dB
Total harmonic distortion	Under 0.6% (at 1 kHz)	Under 0.6% (at 1 kHz)
Dimensions (mm)	480 x 45 x 232 (1 u rack)	221 x 40 x 152
Frequency response	50 ~ 18,000 Hz, ±3 dB	50 ~ 18,000 Hz, ±3 dB

Wall Antenna

UB-900

C/ Barcelona 101
17003 Girona (Spain)
(+34) 972 203 300
OPTIMUS SOUND & COMMUNICATION
www.optimusaudio.com