RECEPTORES DE MICROFONÍA INALÁMBRICA

MI-RD2CU16 2 canales
MI-RD1CU16 1 canal

Receptores de microfonía inalámbrica de uno o dos canales y con la posibilidad de configurar y sincronizar automáticamente los micrófonos, emparejando las frecuencias, mediante ultrasonidos (sistema REMOSET).

CARACTERÍSTICAS GENERALES
Sistema de microfonía inalámbrica

- Banda de frecuencias 823 ~ 832 MHz y 863 ~ 865 MHz.
- Configuración automática.
- Display en todos los transmisores y receptores.
- Sin interferencias con 4G.
- Hasta 15 micrófonos simultáneos.
- Receptores de 1 y 2 canales diversity.
- Micrófonos de mano, solapa, diadema, aeróbic y sobremesa.

MI-RD2CU16

MI-RD1CU16

Modo de Oscilación	phase-locket loop (PLL)
Ajuste remoto	por ultrasonidos
Diversity	antena diversity
Ancho de banda	2 MHz
Relación Señal / Ruido	> 105 dB
THD	< 0.6 % @ 1 kHz
Sensibilidad de recepción	-95 dBm, S/N > 80 dB
Respuesta en frecuencia	50 Hz ~ 16 kHz ± 2 dB
Antena	½" BNC desmontable, 12 ~ 15 Vcc / 100 mA
Niveles de audio	jack de 6.35 mm: -10 dBV, XLR: -4 dBV (Línea) / -24 dBV (MIC)
Impedancia de salida de audio	600 Ω
Output Port	XLR simétrico y Jack 6,35 mm asimétrico (por canal)
Alimentación	12 ~ 15 Vcc (fuente incluida)
Dimensiones (mm)	212,3 x 38,3 x 144

www.optimusaudio.com
C/ Barcelona 101
17003 Girona (Spain)
(+34) 972 203 300
OPTIMUS SOUND & COMMUNICATION

WIRELESS MICROPHONE RECEIVERS

MI-RD2CU16 2 channels
MI-RD1CU16 1 channel

Receivers of wireless microphones of one or two channels and with the possibility of automatically configuring and synchronizing the microphones, matching the frequencies, with ultrasounds (REMOSET system).

MAIN FEATURES
Wireless microphone system

- Frequency band :823 ~ 832 MHz and 863 ~ 865 MHz.
- Automatic configuration.
- Display on transmitters and receivers
- No interference with 4G.
- Up to 15 simultaneous microphones.
- Receptors of 1 and 2 channels with diversity.
- Hand-held, lavalier, stage, aerobic and desk microphones.

MI-RD2CU16

MI-RD1CU16

Frequency Oscillation	phase-locket loop (PLL)
Remote set	ultrasonic
Diversity	antenna diversity
Bandwidth	2 MHz
Signal / Noise Ratio	> 105 dB
THD	< 0.6 % @ 1 kHz
Receiving Sensitivity	-95 dBm, S/N > 80 dB
Frequency Response	50 Hz ~ 16 kHz ± 2 dB
Antenna	½" BNC detachable, DC 12 ~ 15 V / 100 mA
Audio Frequency Output Level	6.35 mm Jack：-10 dBV, XLR：-4 dBV (Line) / -24 dBV (MIC)
Impedance	600 Ω
Output Port	XLR balanced & 6.35 mm jack unbalanced (per channel)
Power Supply	12 ~ 15 Vdc (power supply included)
Dimensions (mm)	212.3 x 38.3 x 144

www.optimusaudio.com
C/ Barcelona 101
17003 Girona (Spain)
(+34) 972 203 300
OPTIMUS SOUND & COMMUNICATION