

PB15

1.5m - 180° AIR Beam Tower (single sided) including installation kit.

Pillar packing list

1. Top/bottom cover : 2 pcs
2. Polycarbonate cover : 1 pcs
3. Aluminium profile : 1 pcs
4. Tamper plate : 1 pcs (EP1)
5. Tamper : 1 pcs (EP1)
6. M3 DIN 934 : 2 pcs (EP1)
7. M3x16 DIN 84 : 2 pcs (EP1)
8. M4x8 DIN 84 : 4 pcs (EP3)
9. M4x20 DIN 933 : 2 pcs (EP2)
10. M4 DIN 934 : 10 pcs (EP3) (C3)
11. M4 DIN 985 : 2 pcs (EP2)
12. M4 DIN 125 : 2 pcs (EP2)
13. Spacer : 2 pcs (EP2)
14. Cable gland PGM16 : 1 pcs (EP3)
15. Cable gland PGM20 : 1 pcs (EP3)
16. M8x16 DIN933 : 4 pcs (TA3)
17. Side bracket <2m : 2 pcs
18. M8 DIN 985 : 4 pcs (TA3)
19. M8 DIN 125 : 4 pcs (TA3)
20. M4x12 DIN 7985 : 6 pcs (C3)
21. Bracket : 3 pcs
22. dia.2.9x16 DIN 7981 : 6 pcs (C3)
23. Anchor bolt : 4 pcs (MAN2)



Standard Features

- 1.5m height
- 180° view
- CE certified product

PB15

1.5m - 180° AIR Beam Tower (single sided) including installation kit.

Specifications

| | |
|------------------------------|---|
| General | |
| Accessory group | Perimeter / Outdoor |
| Type | Mounting |
| Electrical | |
| Operating voltage | 12 to 24 V |
| Power supply type | VDC |
| Physical | |
| Physical dimensions | 1470 x 130 x 150 mm |
| Net weight | 4.35 kg |
| Environmental | |
| Operating temperature | -15 to 50 °C |
| Voltage | |
| | 12 to 24 VDC |
| Angle of view | |
| | 180° |
| Tamper switch output | |
| | CO (change over) |
| Operating temperature | |
| | -15 to +50°C |
| Material | |
| | Aluminium, plastic (polycarbonate, ABS) |
| Dimensions (HxWxD) | |
| | 147 x 13 x 15cm |
| Weight | |
| | 4.35 kg |

Ordering Information

| Part No. | Description |
|------------|---|
| PB15 | 1.5m - 180° AIR Beam Tower (single sided) including installation kit. |
| PB20-SB | Spare side brackets for 1-2m pillars |
| PB50-WB | Wall bracket for 180° beam tower |
| PB50-FB | Floor bracket for concrete (difficult grounds) for 180° and 360° beam towers |
| PB50-AC180 | Anti climb top tamper for 180° beam towers |
| PB34 | |
| PB51 | Bracket kit for mounting beam, power supply or battery for PB pillars (pack of 2) |
| SB52 | Power Supply 230VAC to 12VAC & 12VDC |
| BS121N | Battery 12 V 1,2 Ah |
| PB50-T | Thermostat for beam tower |
| PB50-H | 12V non polarity heater 250mA for beam tower |