

PB16

1.5m - 360° AIR Beam Tower (double sided) including installation kit.

Pillar packing list

1. Top/bottom cover : 2 pcs 2. Polycarbonate cover : 2 pcs

3. Aluminium profile: 1 pcs

4. Tamper plate: 1 pcs (EP1)

5. Tamper: 1 pcs (EP1)

6. M3 DIN 934: 2 pcs (EP1)

7. M3x16 DIN 84 : 2 pcs (EP1)

8. M4x8 DIN 84 : 4 pcs (EP4) 9. M4x20 DIN 933 : 2 pcs (EP2)

10.M4 DIN 934: 16 pcs (EP4) (C3)

11.M4 DIN 985 : 2 pcs (EP2)

12.M4 DIN 125 : 2 pcs (EP2)

13.Spacer : 2 pcs (EP2)

14.Cable gland PGM16: 2 pcs (EP4)

15.Cable gland PGM20 : 2 pcs (EP4)

16.M8x16 DIN933: 4 pcs (TA3)

17.Side bracket <2m: 2 pcs

18.M8 DIN 985: 4 pcs (TA3)

19.M8 DIN 125: 4 pcs (TA3)

20.M4x12 DIN 7985 : 12 pcs (C3)

21.Bracket: 6 pcs

22.dia.2.9x16 DIN 7981 : 12 pcs (C3)

23.Anchor bolt: 4 pcs (MAN2)



Standard Features

- 1.5m height
- 360° view
- CE certified product

PB16

1.5m - 360° AIR Beam Tower (double sided) including installation kit.

Specifications

| General | |
|-----------------------|---|
| Accessory group | Perimeter / Outdoor |
| Туре | Mounting |
| Electrical | |
| Operating voltage | 12 to 24 V |
| Power supply type | VDC |
| Physical | |
| Physical dimensions | 1470 x 130 x 260 mm |
| Net weight | 5.70 kg |
| Environmental | |
| Operating temperature | -15 to 50 °C |
| Voltage | |
| | 12 to 24 VDC |
| Angle of view | |
| | 360° |
| Tamper switch output | |
| | CO (change over) |
| Operating temperature | |
| | -15 to +50°C |
| Material | |
| | Aluminium, plastic (polycarbonate, ABS) |
| Dimensions (HxWxD) | |
| | 147 x 13 x 26cm |
| Weight | |
| | 5.70 kg |
| | |

Ordering Information

| Part No. | Description |
|------------|---|
| PB16 | $1.5\mbox{m}$ - $360\mbox{°}$ AIR Beam Tower (double sided) including installation kit. |
| PB20-SB | Spare side brackets for 1-2m pillars |
| PB50-FB | Floor bracket for concrete (difficult grounds) for 180° and 360° beam towers |
| PB50-AC360 | Anti climb top tamper for 360° beam towers |
| PB34 | |
| PB51 | Bracket kit for mounting beam, power supply or battery for PB pillars (pack of 2) $$ |
| SB52 | Power Supply 230VAC to 12VAC & 12VDC |
| BS121N | Battery 12 V 1,2 Ah |
| PB50-H | 12V non polarity heater 250mA for beam tower |
| PB50-T | Thermostat for beam tower |

