

PB21

2m - 360° AIR Beam Tower (double sided) including installation kit.

Pillar packing list

1. Top/bottom cover : 2 pcs 2. Polycarbonate cover : 2 pcs

3. Aluminium profile: 1 pcs 4. Tamper plate: 1 pcs (EP1)

5. Tamper : 1 pcs (EP1)

6. M3 DIN 934: 2 pcs (EP1)

7. M3x16 DIN 84 : 2 pcs (EP1)

8. M4x8 DIN 84 : 4 pcs (EP4)

9. M4x20 DIN 933 : 2 pcs (EP2) 10.M4 DIN 934 : 20 pcs (EP4) (C3)

11.M4 DIN 985 : 2 pcs (EP2)

12.M4 DIN 125 : 2 pcs (EP2)

13.Spacer : 2 pcs (EP2)

14.Cable gland PGM16: 2 pcs (EP4)

15.Cable gland PGM20 : 2 pcs (EP4)

16.M8x16 DIN933: 4 pcs (TA3)

17.Side bracket <2m: 2 pcs

18.M8 DIN 985: 4 pcs (TA3)

19.M8 DIN 125: 4 pcs (TA3)

20.M4x12 DIN 7985 : 16 pcs (C3)

21.Bracket: 8 pcs

22.dia.2.9x16 DIN 7981 : 16 pcs (C3)

23.Anchor bolt: 4 pcs (MAN2)



Standard Features

- 2m height
- 360° view
- CE certified product

PB21

2m - $360^{\circ}\,\text{AIR}$ Beam Tower (double sided) including installation kit.

Specifications

General	
Accessory group	Perimeter / Outdoor
Туре	Mounting
Electrical	
Operating voltage	12 to 24 V
Power supply type	VDC
Physical	
Physical dimensions	1970 x 130 x 260 mm
Net weight	7.50 kg
Environmental	
Operating temperature	-15 to 50 °C
Voltage	
	12 to 24 VDC
Angle of view	
	360°
Tamper switch output	
	CO (change over)
Operating temperature	
	-15 to +50°C
Material	
	Aluminium, plastic (polycarbonate, ABS)
Dimensions (HxWxD)	
	197 x 13 x 26cm
Weight	
	7.50 kg

Ordering Information

Part No.	Description
PB21	2m - 360° AIR Beam Tower (double sided) including installation kit.
PB20-SB	Spare side brackets for 1-2m pillars
PB50-FB	Floor bracket for concrete (difficult grounds) for 180° and 360° beam towers
PB50-AC360	Anti climb top tamper for 360° beam towers
PB34	
PB51	Bracket kit for mounting beam, power supply or battery for PB pillars (pack of 2)
SB52	Power Supply 230VAC to 12VAC & 12VDC
BS121N	Battery 12 V 1,2 Ah
PB50-H	12V non polarity heater 250mA for beam tower
PB50-T	Thermostat for beam tower

