

CODE: **PS-604812 v1.0/II**

TYPE: **PS 48V/1,2A enclosed switch mode power supply**



Features of the power supply unit:

- power output 1,2A/48÷53V DC*
- wide AC input voltage range 85÷264V
- high efficiency 81%
- LED optical signalisation
- protections:
 - SCP short-circuit protection
 - overvoltage OVP
 - overvoltage protection
 - overload (OLP)
- warranty – 2 year from the production date

DESCRIPTION

The power supply unit is intended for the feeding of alarm system equipments, which require 24V DC supply voltage and current load **I=1,2A**. The design enables simple changing of the output voltage, within the range of 48V÷53V DC, using a potentiometer. The power supply unit is protected against short-circuit, overload and overvoltage.

TECHNICAL DATA

Supply voltage	85 ÷ 264V AC, 120 ÷ 370V DC
Current consumption	0,6A@230V AC max.
Supply power	60W max.
Efficiency	81%
Output voltage	48V DC
Output current $t_{AMB} < 30^{\circ}\text{C}$	1,2 A - see graph 1.
Output current $t_{AMB} = 40^{\circ}\text{C}$	0,9 A - see graph 1.
Voltage adjustment range	48V ÷ 53V DC
Ripple voltage	150mV p-p max.
Short-circuit protection SCP	electronic, automatic recovery
Overload protection OLP	105 -150% of power supply, automatic recovery
Surge protection	varistors
Oversupply protection OVP	>60V (automatic return)
Optical signalisation	green LED – presence of DC voltage
Operation conditions	2-nd enviromental class, temperature: $-10^{\circ}\text{C} \div +40^{\circ}\text{C}$ relative humidity 20%...90%, without condensation
Dimensions	L=159, W=97, H=38 [+- 2mm]
Net/gross weight	0,48kg / 0,5kg
Protection class PN-EN 60950-1:2007	I (first) – requires a protective conductor (PE)
Connectors	power-supply:Φ0,63-2,50 (AWG 22-10) outputs: Φ0,63-2,50 (AWG 22-10)
Declarations, warranty	CE, 2 year from the production date

* In order to extend the life of the power supply, the load current of 0,9A is recommended.


* See graph 1.

PS series power supply

Enclosed, 48VDC switch mode power supply



Output current vs temperature



Graph 1.
Allowable output current from the power supply depending on ambient temperature (instantaneous load).

Dimensions and fitting of the PS-604812 power supply

