

# PSDC series power supply unit

Power supply 12V DC for up to 4 HD cameras



CODE: **PSDC04124** v.1.3/XII  
TYPE: **PSDC 12V/4A/4x1A** power supply for up to 4 HD cameras  
- PTC/TOPIC.

EN\*\*



## Features:

- the 4x 1A/12VDC power output for powering 4 HD cameras
- output voltage adjustment 12V÷ 15VDC
- 4 outputs, protected with 1A fuses
- jumper selectable fuses: glass fuse or polymer fuse
- wide range of supply voltage 85÷264VAC
- high efficiency 80%
- LED indication
- FPS technical output of fuse activation indication
- protections:
  - SCP short-circuit protection
  - OVP over voltage protection
  - surge protection
  - OLP overload protection
  - against tampering
- warranty – 3 year from the production date

## DESCRIPTION

The **PSDC04124** stabilized power supply is designed to supply HD cameras or other devices requiring stabilized voltage of **12V DC**. The output voltage adjustment range is adjusted via a potentiometer within the range of **12V÷15V DC**. The PSU features 4 outputs protected independently by either glass fuses or polyswitches. A failure (a short circuit) in the output circuit makes a fuse blow or an activation of the polymer fuse and disconnection of the circuit from the DC power supply (+U). The PSU is housed in a metallic enclosure with an indication panel featuring a microswitch indicating unwanted opening of the door (faceplate).

# PSDC series power supply unit

Power supply 12V DC for up to 4 HD cameras



| SPECIFICATIONS   |   |
|--|---|
| Power supply   | 85 ÷ 264V AC  |
| Current consumption  | 0,6A@230V AC max.   |
| PSU power  | 60W max.  |
| Efficiency   | 80%   |
| Output voltage   | 12V DC  |
| Output current   | <b>4 x 1A</b>   |
| Output voltage adjustment range  | 12V÷ 15V DC   |
| Ripple voltage   | 100mV p-p max.  |
| Short-circuit protection SCP   | LB4/AW STRIP<br>4x F 1A (fuse) or PTC 1A<br>PSU MODULE<br>105% ÷ 150% of PSU power, electronic current limiting |
| Overload protection OLP  | 105% ÷ 150% of PSU power, electronic current limiting   |
| Surge protection   | varistors   |
| Surge over voltage protection OVP  | >16V (automatic recovery)   |
| Tampering protection system<br>- TAMPER – indicating unwanted opening of the PSU's enclosure       | - microswitch, NC contacts (enclosure closed), 0,5A@50V DC (max.)   |
| Technical outputs:<br>- FPS outputs indicating fuse failure (blow), strips LB4/AW (SCP activation) | - OC type, 50mA max,<br>normal status: L level (0V),<br>failure: hi-Z level                                     |
| LED indication   | LEDs  |
| Operating conditions   | 2nd environmental class, temperature: -10 °C+50 °C, relative humidity 20%...90%, without condensation           |
| Enclosure  | Steel plate DC01 0,7mm thick, colour: RAL9003   |
| Dimensions:  | W=230, H=177, D+D <sub>1</sub> =52+8 [+/- 2 mm]<br>W <sub>1</sub> =234, H <sub>1</sub> =181 [+/- 2 mm]          |
| Net/gross weight   | 1,3/1,4 kg  |
| Closing  | Cheese-head screw: at the front   |
| Declarations, warranty   | CE, 3 year from the production date   |
| Notes  | The enclosure does not adjoin the assembly surface so that cables can be led.<br>Convictional cooling.          |