

# PSDCR series power supply unit


Power supply 12V DC for up to 8 HD cameras with a recorder space



EN\*\*

CODE: **PSDCR08128** v.1.0/I

TYPE: **PSDCR 12V/8A/8x1A/TOPIC** Power supply for up to 8 HD cameras with a recorder space.



## Features:

- the 8x1A/12V DC power output for powering 8 HD cameras
- output voltage adjustment 12V÷15V DC
- 8 outputs protected with 1A fuses
- recorder space 400x345x100
- wide range of supply voltage 176÷264V AC
- high efficiency 83%
- LED indication
- protections:
  - SCP short-circuit protection
  - OVP over voltage protection
  - surge protection
  - OLP overload protection
- warranty – 2 year from the production date

## DESCRIPTION

The **PSDCR08128** stabilized power supply is designed to supply HD cameras or other devices requiring stabilized voltage of **12V DC**. The output voltage adjustment is adjusted via a potentiometer within the range of **12V÷15V DC**. The PSU features 8 outputs protected independently by either glass fuses. A failure (a short circuit) in the output circuit makes a fuse blow and disconnection of the circuit from the DC power supply (+U). The power supply unit is placed in a metal enclosure (color RAL 9003) with space a recorder. A micro switch indicates door opening (front cover).

# PSDCR series power supply unit

Power supply 12V DC for up to 8 HD cameras with a recorder space



SPECIFICATIONS	
Supply voltage	176 ÷ 264V AC
Current consumption	0,8A@230VAC max.
PSU power	96W max.
Efficiency	83%
Output voltage	12V DC
Output current	8x 1A ( $\Sigma$ I= 8A) max.@12V
Output voltage adjustment range	12V÷ 15V DC
Ripple voltage	100mV p-p max.
Short-circuit protection SCP	LB8 STRIP 8x F 1A fuse PSU MODULE 105% ÷ 150% of PSU power, electronic current limiting
Overload protection OLP	105% ÷ 150% of PSU power, electronic current limiting
Surge protection	varistors
Surge over voltage protection OVP	>16V (automatic recovery)
LED indication	LEDs
Operating conditions	1nd environmental class, temperature: -10 °C÷40 °C
Enclosure	Steel plate DC01 0,7mm thick, colour: RAL9003
Dimensions	432 x 607 x 103+14 (WxHxD) [mm] (+/- 2)
Net/gross weight	7,6/8,4 kg
Closing	2 x Cheese-head screw: at the front
Declarations, warranty	CE, 2 year from the production date
Notes	The enclosure does not adjoin the assembly surface so that cables can be led. Convectonal cooling.