



Product data sheet

SMA-VP-MD

Idemia VisionPass MD Facial Recognition reader Bio/Card/PIN/BioPIN (20K users and 40K with license) with MIFARE/ DESFire. Requires MorphoManager software and OAAP

VisionPass

VisionPass is the newest addition to IDEMIA's range of frictionless biometric access control devices, and the most powerful facial recognition device in the market. Elaborated in collaboration with partners and end-users, this robust and reliable device provides near-motion 1-second verification through multiple angles and in all light conditions, and is resistant to all kinds of spoofing attempts.

Integration

Following COVID-19, facial recognition has become of increase interest and through the LenelS2 OAAP program, VisionPass is integrated with OnGuard to enable contactless access control.

Unique performances

VisionPass combines a state-of-the-art optical set of 2D/3D/infrared cameras with IDEMIA's latest advances in AI and image processing, enabling a high level of security and real user convenience.

True security

VisionPass incorporates IDEMIA's latest spoof detection mechanisms and is thus resistant to spoofing attempts. It copes with face changes (helmet, headset, change of haircut, glasses, etc.)

Easy deployment

VisionPass can be deployed at any location: indoor (wall or gate-mounted) or outdoor (IP65 rated). The device reuses many of the technology bricks used in other devices such as MorphoWaveTM Compact, thus simplifying its integration among a fleet of devices.

Performance, security and convenience

State-of-the-art optical set combining 2D, 3D and infrared cameras and stereoscopic image processing algorithm to provide :

› High performance: near-motion 1-second matching with up to 40,000 users

› Resistance to spoofing attempts: picture, 3D mask...

› Efficiency in all light conditions: from complete obscurity to sunlight

Developed in collaboration with installers to provide :

› Easy installation through a VESA standard back cover

› Reuse of proven hardware and software bricks already used in SIGMA and MorphoWave ranges, simplifying integration

› Compatibility with IDEMIA's MorphoManager device management platform and plug-and-play with most access control systems

The most powerful facial recognition device

Combining years of experience in the development of facial recognition algorithms and devices for the most demanding applications (governments, airports...) with its latest advances in AI, IDEMIA proposes the most powerful facial recognition device for the access control market.



Details

- Stylish, functional design
- 7" WVGA color capacitive touchscreen
- Frictionless biometric access solution
- Timed anti-pass back function
- Banned/authorized user lists
- Standalone integration or in line with turnstiles
- Mitigates hygiene concerns
- Robust against external light and dust
- Touchscreen time clock, featuring 16 programmable function keys + 4 dedicated function keys
- Fully handsfree: no need to interact with the device
- Extensive customization capabilities: user dedicated messages, corporate video, wallpapers
- Time & Attendance features, including: * Programmable function keys (Entry, Exit, Beginning of task, Ending of task) * Real-time employee notifications * Job Code management
- Ideal for high throughput and high security applications
- Access time slots and holiday scheduling
- Real-time employee notifications
- Ingenious, symmetrical opening mechanism enables easy wall-mounting and in-place maintenance
- High performance: near-motion 1-second matching with up to 40,000 users
- Efficiency in all light conditions: from complete obscurity to strong sunlight
- Wide angle detection for persons of all sizes (1.20-2.00m) and side approach

SMA-VP-MD

Idemia VisionPass MD Facial Recognition reader Bio/Card/PIN/BioPIN (20K users and 40K with license) with MIFARE/ DESFire. Requires MorphoManager software and OAAP

Technical specifications

Technology

| | |
|---|--|
| Reader type | BioMetric |
| Reader operating-transmitting frequency | 13.56 MHz |
| Supported technology 13.56 MHz | MIFARE Classic (CSN), MIFARE DESFire (CSN), MIFARE DESFire EV1 (CSN), MIFARE DESFire EV1 (custom data), Mifare DESFire EV2 (CSN) |
| Touchless face sensor | Visible light camera (2D) |
| Touchless face sensor | Infrared camera (2D) |
| Touchless face sensor | 3D camera |

System

| | |
|-------------------------------|--------------------------------|
| Max. reader distance to panel | Ethernet: 100 m, RS485: 1219 m |
| CSN (Card Serial Number) | Yes |
| Custom data model | Yes |

Biometric

| | |
|---------------------------------|--|
| Biometric type | Facial Recognition |
| Biometric sensor type | Optical |
| Biometric template storage size | 20.000 Upgrade to 40,000 with SMA-VP-DB-40K |

Interface & connections

| | |
|----------------|---|
| Interface | Ethernet, OSDP V2, OSDP V2 Secure Channel, RS-485, USB, Wiegand |
| Connector type | Network, Terminal Strip, USB |

Tamper type

| | |
|----------------|-----|
| Opening tamper | Yes |
|----------------|-----|

Operation

| | |
|--------------------------|--------------------------------------|
| Stand-alone | Yes |
| Stand-alone no. of users | 20,000 |
| PIN keypad | Yes |
| MorphoManager | Supported from MorphoManager v14.4.3 |

Support

| | |
|------------------------------|---------|
| Language installation manual | English |
|------------------------------|---------|

Electrical

| | |
|---------------------|--|
| Power supply type | VDC |
| Power supply value | 12 to 24 VDC No Power over Ethernet |
| Current consumption | 3A min @ 12 VDC |

Physical

| | |
|--------------------------|--|
| Physical dimensions | 325 x 143 x 110 mm |
| Net weight | 2100 g |
| Shipping weight | 2900 g |
| Colour | Silver |
| Material | Polycarbonate |
| Mounting type | Desk mount, Surface mount, VESA mounting bracket, Wall mount |
| Mounting type | VESA mount bracket (Video Electronics Standards Association) |
| Communication | Ethernet, RS485, RS422, USB, Wi-Fi and 4G options |
| Inputs/outputs | Wiegand In & Out (customizable up to 512 bits), Door Relay, 3 GPI (including Door monitoring), 3 GPO |
| CPU | Nvidia ARM Cortex-A15 Quad-Core 2.1GHz |
| Touchscreen | 7" WVGA color capacitive touchscreen |
| Loudspeaker & microphone | Intercom function with SIP, Audio & video player |

Environmental

| | |
|---------------------|---|
| Vandal proof | No |
| Storage temperature | -10 to +45°C |
| Relative humidity | 10% to 80% (non condensing) |
| Environment | Indoor / Outdoor |
| IP rating | IP65 Recommendation for outdoor installation: avoid direct exposure of sensor to rain (e.g., place under a canopy) |

Standards & regulation

| | |
|------------|---|
| Compliance | CE, FCC, FCC Part 15 Class A, REACH, RoHS, WEEE |
|------------|---|

How to order

| | |
|---------------|--|
| SMA-VP-MDPI | Idemia VisionPass MDPI Facial Recognition reader Bio/Card/PIN/BioPIN (20K users and 40K with license) with Mifare/DESFire/Prox/HID iCLASS/iCLASS SEOS. Requires MorphoManager software and OAAP integration. Requires 12 VDC @ 3 A power supply (no PoE), 2 years warranty |
| SMA-VP-ENROLL | Idemia VisionPass Enrollment Bundle, MorphoManager Software, ViP terminal, includes 12 VDC @ 3 A power supply, Cable Connectors to Power Supply, Vesa desktop stand |
| SMA-VP-DB-40K | Idemia VisionPass database upgrade to 40K for MD/MDPI Facial Recognition reader - To upgrade database size to 40K users (vs 20K without license) - S/N or License ID of the target terminal is needed together with the order for License generation |

As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 1 September 2020 - 16:17

