

SR-S4SEB-Q

LINE ARRAY SPEAKER

The SR-S4SWP is a two-way line array speaker ideal for short distance sound transmission and configures a line array by arranging speaker elements vertically close to each other. It satisfies the water protection requirements set down in the IPX4 Standard as well as EN54-24. It can be converted into the bi-amplifier drive system by changing the internal connection. It can be used for high-impedance applications with the installation of the optional MT-S0601 Matching transformer.



Order no: SR-S4SEB-Q
Alternative products: VX-3016F, VM-3240E,
VM-3360E, SX-2100AO, SX-2000AO,
VM-3240VA, VM-3360VA, VP-2064,
VP-2064incl, VP-2122, VP-2122incl, VP-2241,
VP-2241incl, VP-2421, VP-2421incl, VP-3154,
VP-3304, VP-3504, SX-2000SM, VX-3004F,
VX-3008F, VX-2000

Specifications

Frequency response	70 Hz - 20 kHz
Connection	Direct cable withdrawal from internal speaker: ø8.6 mm, conductorcross section: 1.25 mm ² , 4-core cable, 3 m
Sensitivity (1#V, 1#m) (combined)	93 dB
Speaker component	Low frequency: 10 cm cone-type × 8, High frequency: 2.5 cm balanced dome-type × 24
Directivity angle horizontal	90 °
Directivity angle vertical	10 °
Rated impedance	8 Ω
Crossover frequency	4 kHz
Power handling capacity	Continuous program: 600 W
Dimensions (W x H x D)	160 x 892 x 303 mm
Dimensions (ø x D)	x 303 mm
Finish	Plywood, urethane coating, off-white (RAL 9010 or equivalent)

SR-S4SEB-Q
LINE ARRAY SPEAKER

Appearance

