

TVB-5501

TruVision IP Bullet Camera, H.265/H.264, 3MPX

Overview

The TruVision Series 5 line of IP bullet form factor cameras leverages the latest H.265 video compression technology to bring state-of-the-art, high-definition pictures to the mass video surveillance market. With camera resolutions of 3 or 8 megapixel, these IP cameras represent a flexible video surveillance device to meet any need. Equipped with advanced technology and signal processing capability, they effectively capture video under challenging conditions.

TruVision cameras utilize H.264 and/or H.265 compression technology with triple-streaming capability, making it easy to manage the camera's bandwidth usage. Motorized varifocal lens technology allows the user to remotely adjust the varifocal lens length and focus the camera with the touch of a button. Select models feature Low Light technology, which provides a clear image in low lighting conditions with a minimum of "grainy" interference. Recording to a local MicroSD card (not included) protects data in the event of network disruptions.

These cameras go above and beyond standard motion detection with enhanced alarm capabilities, including cross lines, intrusion, de-focus and face detection features. Each is user-configurable to best suit the installation environment. A Region of Interest function ensures specific portions of an image are given priority during instances of high network traffic or network degradation.

Location-specific functions include a Hallway View Mode to provide a portrait view of a hallway or corridor, a De-Fog Mode to help resolve images through fog or rain and Electronic Image Stabilization for installations subject to physical vibration or shaking.



Caratteristiche standard

- Maximum Resolution: 2048 x 1536
- Maximum Real Time Resolution: 2048 x 1536 @ 25/30 fps (50/60 Hz)
- Designed to PSIA and ONVIF Profile G and S open standards
- H.265 and/or H.264 compression with triple-streaming functionality
- Edge recording up to 128GB SDHC card
- 1/2.8 CMOS image sensor
- Motorised IR Cut Filter
- Super Low Light: Color: 0.005 Lux @ (f1.2, AGC ON), 0 Lux IR on
- Fixed Lens 4mm
- Up to 30m IR illumination
- Up to 120dB Wide Dynamic Range
- Intelligence (Face detection, Audio Exception Detection, Intrusion Detection, De-focus Detection, Region of Interest (ROI), Electronic Image Stabilization (EIS), Defog, Scene Change Detection, Cross Line Detection, Advanced Motion Detection, Region Entrance Detection, Region Exit Detection, Object Removal, Object Left Behind, Object Counting)

TVB-5501

TruVision IP Bullet Camera, H.265/H.264, 3MPX

Dati tecnici

Camera	
Sensor Size	1/2.8"
Sensor Scan	Progressive
Sensor Type	CMOS
Max. Resolution	3 MPX
Total Pixels (H x V)	2048 x 1536
Digital S/N ratio (dB)	50 dB (AGC Off)
Electronic Shutter	1/3s - 1/100,000s
Day/Night:	Motorized IR Cut Filter
IP Compression/Standard:	H.265/ H.264 / MJPEG
Maximum Resolution (@ FPS):	2048 x 1536 (25/30 fps)
Maximum Real Time Resolution (@ FPS):	50Hz: 25 fps (2048 x 1536) 60Hz: 60 fps (1920 x 1080, 1280 x 960, 1280 x 720)
Multiple Streaming:	Triple Streams
Video Bit Rate:	32 Kbps to 16 Mbps, adjustable
Composite Output (BNC):	N/A
Lighting performance	
Wide dynamic range (WDR)	True WDR
WDR	120 dB
Digital Noise Reduction	3D DNR
Day/Night	True Day/Night
Motorized IR Cut Filter	Yes
Color Sensitivity	0.009 lux @ (F1.6, AGC ON); 0 lux with IR
B/W Sensitivity	0 lux with IR on
InfraRed (IR)	Yes
IR Sensitivity	0 lux with IR
IR Range	Up to 30 m
Wide Dynamic Range	WDR
Lens	
Focal length	4mm
F-stop	f1.6
Auto-iris	Yes
Lens Type	Fixed
Network	
Supported Network Protocols	802.1x, DDNS, DHCP, DNS, FTP, HTTP, HTTPS, IPv4, IPv6, NTP, PPPoE, Qos, RTP, RTSP, SMTP, SNMP, TCP/IP, UPnP
Supported Video Standards	CGI, ONVIF, PSIA
Network Protocols:	TCP/IP, HTTP, DHCP, DNS, DDNS, ezDDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos, IPv6. ONVIF, PSIA, CGI
PoE IEEE:	802.3at
Standard & Integration:	ONVIF Profile (G,S), PSIA, CGI
Audio	
Audio In	N/A
Audio Out	N/A
Alarm I/O	
Alarm Outputs	N/A
Storage	
Max Storage Capacity	128GB
Local Storage Support	Yes
Local Storage Type	Built-in Micro SD/SDHC/SDXC card slot
Video intelligence	
Basic Alarm Detection	Motion, Privacy Masking, Tamper
Video Analytics	Advanced motion detection, Audio exception, Cross line, De-focus, Defog, Electronic Image Stabilization (EIS), Face detection, Intrusion detection, Object counting, Object left behind, Object removal, Region entrance detection, Region exit detection,
General	
Technology	IP
Display Modes	Hallway View, Mirror, ROI (Region Of Interest)

Software Compatibility	OnGuard, Prism, TruVision Navigator, TVRmobile, Web Browser
Electrical	
Power supply type	PoE in, VDC
Power supply value	12 VDC
Power consumption	6 W
Current consumption	0.56 A
Physical	
Form Factor	Bullet
Physical dimensions	70 x 155 mm
Net weight	410 g
Colour	Grey
Environmental	
Operating temperature	-30 to +60°C -22 to +140°F
Storage temperature	-30 to +60°C -22 to +140°F
Relative humidity	<95% (non-condensing)
Vandal proof	No
Environment	Outdoor
IP-rating	67
Standards & regulation	
Compliance	CE, FCC, HALT, REACH, RoHS, UL, WEEE
LocalStorage	
Media:	MicroSD/micro SDHC/ microSDXC
Capacity:	Up to 128GB
Regulation	
Compliance:	FCC, CE, UL, WEEE, RoHS, REACH

Come ordinare

Codice prodotto	Descrizione
TVB-5501	TruVision IP Bullet Camera, H.265/H.264, 3MPX

