

TVD-2403

TruVision HD-TVI Analog Dome Camera, PAL, 1080p, 2.8 mm lens

Overview

The new TruVision line includes a comprehensive family of HD-TVI infrared (IR) cameras for stand-alone or integrated installations, designed for optimal image quality over existing coaxial cable.

Ideal for improving video quality of existing analog surveillance system installations ranging from convenience stores to retail mall parking lots, the TruVision HD-TVI line has the right cameras for your new or existing project and can help you stay within budget constraints without compromising security needs.

The cameras have true day/night capabilities, providing color images by day and black-and-white images under IR operation in low light applications. TruVision HD-TVI cameras are available with either fixed lens or varifocal lens.

Form factors include dome and traditional bullet cameras. Bullet models offer a familiar form factor that features a pre-installed wall mount with cable management. All models are IP66 rated for outdoor installation and select dome models are available with an IK10 vandal-rated enclosure.

All TruVision HD-TVI cameras are designed to install quickly and easily, right out of the box, so you can be up and running in no time.



Standard Features

- 1080p HD resolution
- HD-TVI technology for transmitting HD quality video over existing coax cable
- True day/night functionality and infrared illuminators with Smart IR function for capturing images in various lighting scenarios
- IR range of up to 20 m
- IP66 environmental rating
- Wide dynamic range
- 2.8 mm fixed lens
- 12 VDC
- Provide OSD control via TruVision up the coax and built-in menu button

TVD-2403

TruVision HD-TVI Analog Dome Camera, PAL, 1080p, 2.8 mm lens

Specifications

Camera	
Max. Resolution	1080p
Pick-up device:	1/3" Progressive Scan CMOS
Total pixels (H x V):	1920 × 1080
Effective pixels (H x V):	1920 × 1080
Resolution:	1080p
Sync. system:	Internal
S/N ratio:	More than 52 dB
Electronic shutter:	1/25 to 1/50,000 s
Day/Night:	True Day/Night
Motorized IR cut filter:	Yes
Color sensitivity:	0.01 Lux @ (F1.2, AGC ON), 0.034 Lux @ F2.2, AGC ON)
B/W sensitivity	0 Lux with IR on
Video output:	Dual HD-TVI or 960H
IR distance:	Up to 20 m
Lens type:	Fixed: 2.8 mm @ F2.2
Wide dynamic range:	120 dB
Digital noise reduction	3D DNR
OSD:	Built-in OSD button, TruVision Coax OSD control on both HD-TVI and 960H
Lighting performance	
InfraRed (IR)	No
Network	
Supported Video Standards	CGI, ONVIF, PSIA
Storage	
Local Storage Support	No
General	
Technology	HD-TVI analog
Video Standard	PAL
Electrical	
Power source:	12 VDC
Power consumption:	4 W (max.)
Current:	300 mA
Physical	
Form Factor	Dome
Physical dimensions	111 x 82 mm
Environmental	
Operating temperature	-30 to 60°C
Storage temperature	-20 to +70°C -4 to +158°F
Environment	Outdoor
Environmental & Physical	
Weight:	345 g (0.761lbs)
Dimensions:	111 x 82 mm (4.4 x 3.2 in.)
Operation temperature:	-30 to +60 °C (-22 to +140 °F)
Storage temperature:	-20 to +70° C (-4 to +158° F)
Environmental rating:	IP66
Accessory	
Coax OSD controller:	TVS-C200

Ordering Information

Part No.	Description
TVD-2403	TruVision HD-TVI Analog Dome Camera, PAL, 1080P, 2.8mm lens, true D/N, WDR, 20m IR, Dual output 960H or HD-TVI , Coax OSD control, 12VDC, IP66, Plastic

