

TVM-4002

TRUVISION 40" LED, VGA, HDMI, BNC, Audio Speaker, Stereo Audio In, FULL HD, 1920X1080



Details


- 40" LED Backlight
- Full HD resolution
- 16:9 aspect ratio
- 1920 x 1080 recommended resolution
- 5,000:1 contrast ratio for crisp images
- 3D comb filter for optimal image quality
- Multiple inputs including BNC, VGA, HDMI
- BNC analog input

TVM-4002

TRUVISION 40" LED, VGA, HDMI, BNC, Audio Speaker, Stereo Audio In, FULL HD, 1920X1080

Technical Specifications

	00.5
Screen Size	39.5"
Aspect Ratio	16:9
Contrast Ratio	5,000:1
Viewing Angle (H/V)	178° / 178°
Response Time	8ms
Brightness	360 cd/m² (typ)
Video Compatibility	NTSC/PAL Auto Detect
Recommended Resolution	1920 X 1080 @ 60 HZ
Audio	
Speaker Power	2W x 2
Speakers	Built-in
Interface	
BNC Video I/O	1/1
VGA Video In (15-pin d-	Yes
sub)	
HDMI Video In	1
RCA Audio In	1
PC Stereo In	Yes
Head Phone Out	No
Operations	
Controls	Power, Up/Down, Left/Right, Source, OSD Menu
OSD	English, French, Spanish, German, Italian, Portuguese, Netherlands, Russian, Turkish Polish
Remote Control Support	Yes
General	
Technology	LED
VESA compatibility	100 x 100 mm
Filter Type	3D Combfilter, Deinterlace
Accessories Included	Manual, Power Cord, Remote Control
Panel Lamp Life	30,000 hours
Electrical	
	100 to 240 VAC
Power supply type Power consumption	100 to 240 VAC <60W
Power supply type Power consumption	
Power supply type Power consumption Physical	<60W
Power supply type Power consumption Physical Physical dimensions	<60W 907mm x 610 mm x 245mm
Power supply type Power consumption Physical Physical dimensions Net weight	<60W 907mm x 610 mm x 245mm 11 kg
Power supply type Power consumption Physical Physical dimensions Net weight Shipping weight	<60W 907mm x 610 mm x 245mm 11 kg 13.8 kg
Power supply type Power consumption Physical Physical dimensions Net weight Shipping weight Colour	<60W 907mm x 610 mm x 245mm 11 kg 13.8 kg Black
Power supply type Power consumption Physical Physical dimensions Net weight Shipping weight Colour Housing Type	<60W 907mm x 610 mm x 245mm 11 kg 13.8 kg
Power supply type Power consumption Physical Physical dimensions Net weight Shipping weight Colour Housing Type Environmental	<60W 907mm x 610 mm x 245mm 11 kg 13.8 kg Black Plastic
Power supply type Power consumption Physical Physical dimensions Net weight Shipping weight Colour Housing Type Environmental Operating temperature	<60W 907mm x 610 mm x 245mm 11 kg 13.8 kg Black Plastic 0 to 40°C
Power supply type Power consumption Physical Physical dimensions Net weight Shipping weight Colour Housing Type Environmental Operating temperature Storage temperature	<60W 907mm x 610 mm x 245mm 11 kg 13.8 kg Black Plastic 0 to 40°C -20 to 60°C
Power consumption Physical Physical dimensions Net weight Shipping weight Colour Housing Type Environmental Operating temperature	<60W 907mm x 610 mm x 245mm 11 kg 13.8 kg Black Plastic 0 to 40°C



As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

CE

Compliancy

