

TVN-1116-6T

TruVision NVR 11, 16 channels, 160 Mbps, 6 TB

Overview

TruVision NVR 1116 (TVN 1116) is a cost effective network video recorder for sixteen IP video cameras. With a total of 160 Mbps of incoming bandwidth available, it can support up to sixteen cameras at Full HD resolution (1080P) in real time (25 fps).

Ease of use & flexibility

TVN 11 is designed to be flexible – not only in its deployment and product selection, but also in its day-to-day operations.

The unit can be fully controlled locally using the front panel buttons and mouse, displaying high resolution Full HD video on its local VGA monitor or even at 4K resolution on the HDMI video output.

Alternatively, TVN 11 can be operated remotely using its full featured web browser interface or using the TruVision Navigator and TVRMobile software applications.

TVN 11 is available with 2, 4 and 6 TB onboard storage. Recording options include continuous, event and alarm. The three modes can be combined to ensure that the most flexible and efficient recording method.

H.265

TVN 11 supports both H.264 and H.265 compression techniques. H.265 compression is the next evolution in video encoding. Compared to H.264, using H.265 will reduce the file size for the same video content and reduce transmission bandwidth. This means that less storage capacity is needed by H.265 than H.264 encoding for the same video duration. H.265 encoding in the TVN 11 requires that H.265 TruVision IP cameras are used.

Basic intrusion integration

TVN 11 can receive SIA or XSIA alarm messages from up to three Interlogix IP intrusion panels. Alarm messages, disarming and arming messages can be sent from the alarm panel to the recorder, which then can execute actions (ex; trigger alarm recording, send an email, send a PTZ to a preset, ...). Also the heartbeat message between panel and recorder is monitored. This solution offers straightforward alarm verification and is free of charge.



Details

- Linux embedded Plug and Play configuration
- Supports H.264 and H.265
- Up to 160 Mbps camera recording bandwidth
- Up to sixteen IP channels
- 6 TB embedded storage
- Icon based front panel
- Real time Full HD recording
- Up to 4K resolution support
- Motion detection, VCA, privacy masking and tamper detection
- TruVision IP camera auto-detection
- Third party camera support via ONVIF Profile S or RTSP (custom protocols)
- IP camera configuration import/export
- Integration of UTC IP intrusion panels via SIA/XSIA reporting
- TVK-800 IP keypad support (no support for local display of H.265 cameras)
- USB DVD burner support
- Full browser-, OSD- and software-based access for live, recorded video & configuration
- TVRMobile app for iOS and Android
- TruVision Navigator license-free client/host or standalone application
- External integration through SDK

TVN-1116-6T

TruVision NVR 11, 16 channels, 160 Mbps, 6 TB

Technical specifications

General

Operating system	Embedded Linux
Rack mountable	Yes
Rack stacking size	1 U

Video/audio input

IP camera channels	16
Camera bandwidth	160
Max. IP audio in	16
Max. analog audio in	1
Supported video compression standards	H.264, H.265
Supported video streaming standards	Onvif, RTSP Custom Protocols

Local viewing

HDMI output	1
HDMI version	1.4, 2.0
VGA output	1
Max. local output resolution	4K
Synchronous playback OSD (channels)	Up to 4 channels (1080P)
Reverse playback OSD (channels)	Up to 1 channel

Remote viewing

Total available viewing bandwidth	80
Max. live viewing streams	128 streams
Max. playback viewing streams	8 streams
Max. simultaneous playback web browser	TCP: Up to 32 ch; UDP: Up to 8 ch
Reverse playback web browser (channels)	TCP: Up to 32 ch; UDP: Up to 8 ch
Software compatibility	Advisor Manager, OnGuard, TruVision Navigator, TVRmobile
Browser compatibility	Internet Explorer

Storage

Storage capacity	6 TB
Maximum recording resolution	4 K
Recording modes	Alarm, Event, Manual, Time-lapse high, Time-lapse low
Edge failover recording	No

Networking

Network interface cards (NIC)	1
NIC type	RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface
DNS support	DDNS, ezDDNS, No-IP
HTTPS support	Yes

External interfaces

USB interface back	1
USB interface front	1
Alarm inputs	4
Alarm outputs	1
Max. analog audio outputs	1

Electrical

Operating voltage	12 VDC
Power supply type	12 VDC
Power consumption without HDD (W)	40 W

Physical

Physical dimensions	380 x 320 x 48 mm
Net weight	2 kg
Colour	Black

Environmental

Operating temperature	-10 to +55 °C
Relative humidity	10 to 90% noncondensing

Standards & regulation

Compliance	CE, REACH, RoHS, UL
------------	---------------------

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

Last updated on 25 October 2019 - 16:39