

# TVT-2403

TruVision 5 MPX HD-TVI Turret camera, 2.8 mm fixed lens - PAL



#### Details

- 5MPx HD-TVI resolution
- Motorized 2.8mm fixed lens
- HD-TVI technology for transmitting high quality video over existing coax cable
- TruVision over-the-coax support for efficient remote access to local camera OSD menu and lens configuration
- Digital Wide Dynamic Range (DWDR)
- Built-in IR-illuminators to cover low light scenes up to 20m, including Smart IR function to optimize IR illumination
- IP67 rating for optimal outdoor use
- Multiple mounting options, including Turret mounting plate
- Cable protection/management

# TVT-2403

TruVision 5 MPX HD-TVI Turret camera, 2.8 mm fixed lens - PAL

# **Technical Specifications**

ar		

Max. Resolution	5 MPX
Sensor Scan	Progressive
Sensor Type	CMOS
Total Pixels (H x V)	2592 x 1944
Digital S/N ratio (dB)	>62dB
Electronic Shutter	NTSC: 1/30 s to 1/50,000 s; PAL: 1/25 s to 1/50,000 s

# Lighting performance

Wide dynamic range (WDR)	Digital WDR
Day/Night	True Day/Night
Motorized IR Cut Filter	Yes
B/W Sensitivity	0.01 lux @ f1.2 (AGC On); 0 lux with IR
InfraRed (IR)	Yes
IR Range	20m

## Encoding

1920 x 1080 (1080p), 2592 x 1944
2560 (H) × 1944 (V) @ 12.5 fps

#### Lens

Lens Type	Fixed	
Focal length	2.8mm	
Auto-focus	No	
Motorized Zoom	No	

# Video intelligence

Video Analytics Defect pixel correction, S	Smart IR
--	----------

#### General

Technology	HD-TVI analog	
Video Standard	PAL	
Display Modes	Mirror	
Video Output	BNC Composite	

## Electrical

Operating voltage	12VDC
Power supply type	12 VDC
Power consumption	3W (Max.)
Current consumption	250mA

## Physical

Physical dimensions	$5 \times 3.85$ in. 126.7 $\times$ 97.84mm
Net weight	0.77 lbs. 350g
Colour	Grey (Pantone 428c)
Form Factor	Turret

## Environmental

Vandal proof	No
Operating temperature	-40°~60°
	-40°F~140°F
Cold Start Temperature	-40°~60°
	-40°F~140°F
Relative humidity	<90% (non-condensing)
Environment	Indoor, Outdoor
IP-rating	IP67

# Standards & regulation

|--|



