



ELECTROMAGNETIC LOCKS

► A LARGE RANGE OF ELECTROMAGNETIC LOCKS SUITABLE FOR ALL YOUR NEEDS

V3S - V4S - V5S

Illuminated surface mount electromagnetic locks



V3S
V3SR
V3SRB [WITH BUZZER]

300KG



V4S
V4SR
V4SRB [WITH BUZZER]

400KG



V5S
V5SR
V5SRB [WITH BUZZER]

500KG



The new range of electromagnetic locks with feedback in 300, 400 and 500kg versions, Complies with the "disability act" regulation.


**PATENTED,
BREVETÉ**



Safety ropes included with all surface mount electromagnetic locks

* Refer to Limited Lifetime Warranty Conditions.

- **NF S 61-937.**
- **Surface mount.**
- **Relay/Monitored:** Relay + Lock status (According versions).
- **High resistance to corrosion.**
- **Safety rope.**
- **Delivered with its armature plate.**
- **No mechanical wear.**
- **Easy installation.**
- **Recommended for indoor use.**
- **Fail safe (Door unlocked when the power is cut).**
- **Holding force:**
 - V3S RANGE = 300kg,
 - V4S RANGE = 400kg,
 - V5S RANGE = 500kg,
- **Audible and visual feedback (according to version, see table).**
- **No residual magnetism.**
- **Built-in varistor (Electronic protection to eliminate back EMF).**
- Electromagnetic lock dimensions (L x W x D):
 - V3S RANGE = 254 x 45 x 28mm,
 - V4S RANGE = 254 x 50 x 29mm,
 - V5S RANGE = 273 x 67 x 41mm.
- Armature dimensions (L x W x D):
 - V3S RANGE = 185 x 38 x 11mm,
 - V4S RANGE = 185 x 45 x 12mm,
 - V5S RANGE = 185 x 60 x 12mm.
- Silent operation.
- Optional: Electromagnetic lock accessories (See p. 243).
- Input voltage: 12/24V dc.
- Consumption:
 - 12V dc = 550mA.
 - 24V dc = 275mA.



		Feedback	
Ref.	Holding force	Visual	audible
V3S	300kg		-
V4S	400kg		-
V5S	500kg		-
V3SR	300kg		-
V4SR	400kg		-
V5SR	500kg		-
BUZZER	V3SRB		Yes
	V4SRB		Yes
	V5SRB		Yes

COLOUR CODES:



Recommended power supplies



CODE	REFERENCE	DESCRIPTION
F0526000001	V3S	300-KG SURFACE MOUNT ELECTROMAGNETIC LOCK 12/24V DC - NF S 61-937
F0526000002	V3SR	300-KG SURFACE MOUNT ELECTROMAGNETIC LOCK 12/24V DC + RELAY/MONITORED - NF S 61-937
F0526000016	V3SRB	300-KG SURFACE MOUNT ELECTROMAGNETIC LOCK 12/24V DC + RELAY/MONITORED AND BUZZER - NF S 61-937
F0525000016	V4S	400-KG SURFACE MOUNT ELECTROMAGNETIC LOCK 12/24V DC - NF S 61-937
F0525000015	V4SR	400-KG FLUSH MOUNT ELECTROMAGNETIC LOCK 12/24V DC + MONITORED - NF S 61-937
F0526000017	V4SRB	400-KG SURFACE MOUNT ELECTROMAGNETIC LOCK 12/24V DC + RELAY/MONITORED AND BUZZER - NF S 61-937
F0526000003	V5S	500-KG SURFACE MOUNT ELECTROMAGNETIC LOCK 12/24V DC - NF S 61-937
F0526000004	V5SR	500-KG SURFACE MOUNT ELECTROMAGNETIC LOCK WITH RELAY 12/24 V - NF S 61-937
F0526000018	V5SRB	500-KG SURFACE MOUNT ELECTROMAGNETIC LOCK 12/24V DC + RELAY/MONITORED AND BUZZER - NF S 61-937

* Refer to Limited Lifetime Warranty Conditions.