



MX-6224D

DIGITAL MIXER AMPLIFIER 2X240W

The Ultimate Choice for Mosques

The number of mosques around the world is rapidly increasing however there are very few sound systems that can match their complex needs, as well as their tight budget.

TOA has created the MX-6224D, an affordable digital mixer amplifier, specifically to cater for medium and small mosques. the MX-6224d is a reliable and simple system, needing very little technical knowledge to operate, yet still maintains exceptional sound quality.



Order no: MX-6224D 1CE

Specifications

Power source	220 - 240 V AC, 50 / 60 Hz
Rated output	240 W (2 ch (100 V, 42 Ω , rated output)
Frequency response	50 Hz - 20 kHz (± 3 dB)
Distortion	< 1 %
S/N ratio	60 dB
Number of channels	8
Connectable microphones	6
Inputs	MIC 1: -50 dBV (24 V phantom powered) / -60 dBV (phantom power off), 600 Ω , electronically balanced, 6.3 mm phone jack MIC 2 - 4: -66 dBV, 200 Ω , electronically balanced, 6.3 mm phone jack or XLR MIC 5 - 6: -60 dBV, 600 Ω , electronically-balanced, 6.3 mm phone jack or XLR AUX 1: -10 dBV, 10 k Ω mixed monaural, unbalanced, RCA pin jacks (1 pair) AUX 2: -20 dBV, 10 k Ω mixed monaural, stereo mini jack
Outputs	Speaker output: 2 zones, 100V (42 Ω), galvanic isolated balanced, M4 screw terminal Recording output: 0 dBV, 600 Ω monaural, unbalanced, RCA pin jacks (1 pair) Effect bus output: 0 dBV, 600 Ω monaural, unbalanced, RCA pin jacks (1 pair) Preamplifier output: 0 dBV, 600 Ω monaural, unbalanced, RCA pin jacks (1 each for ROOM and OUTSIDE outputs)
Dimensions (W x H x D)	420 x 99,8 x 360,6 mm
Dimensions (ϕ x D)	x 360,6 mm
Finish	Aluminium, Steel plate, paint, black
Operating humidity	35% to 80%
Operating temperature	0°C to + 40°C

We supply sound, not equipment.
www.toa.eu.

©TOA Electronics Europe GmbH | Data subject to change without notice.
EN, 2020/09/24



MX-6224D

DIGITAL MIXER AMPLIFIER 2X240W

Appearance